

SPEC SHEET

Capsule Filling Machines <228,000 capsules/hour

CF-M 3200, 3800B/C/E MODELS

INTRODUCTION

An automatic capsule filling machine is manufactured and designed to directly fill up capsules with pharmaceutical powders without the need for operator involvement.

CF-M 3200, 3800 series automatic capsule filling machines provide high-volume capsule filling solutions between 192,000 capsules per hour and 228,000 capsules per hour.

KEYWORDS Automatic capsule filling | high-volume capsule filling | hard capsule | capsule filling



ATTRIBUTES

- The CF-M 3200 and 3800 models have enclosed turning tables for easy cleaning
- Single movement for both upper and lower segments with two-lip seal provide a much better sealing performance
- A combined air blowing & suction function on segment cleaning station ensures cleaning efficiency at high speeds
- Dust-preventing rubber block on capsule discharge station

MODEL E HAS THE FOLLOWING CHARACTERISTICS:

- Control system is provided with OPC Server.
- Control system includes FDA CFR211 e-signature and e-recording for work monitoring purposes. Specific user accounts can be created for data and quality management.
- Control system is provided with an industrial grade ethernet interface that connects with the OPC Client.
- A high-capacity hard drive for data recording, meeting current GMP and FDA (Food and Drug Administration) standards.

TECHNICAL PARAMETERS

Model	CF-M 3200 B/C/E	CF-M 3800B/C/E
Max. Output	192,000 capsules/hour	228,000 capsules/hour
Number of Die Holes	23	27

Machine Specs (All Models)	Filling Dosage Form	Powder, Pellets, Tablet
	Capsule Size	Capsule size 00# - 5# and safety capsule A-E
	Motor Power	6.37kw
	Power Supply	AC 380V; 50Hz
	Noise	≤78dBA
	Vacuum Degree	-0.02~-0.06 MPa
	Compressed Air (clean segment)	Air consumption: 6m ³ /h Pressure: 0.3~0.4 MPa
	Dimensions	1390×1300×2080mm
	Weight	2400kg



Model B



Model C



Model E

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.