

## SPEC SHEET

# Fixed Type Homogenizing Emulsifier

## SME-B Series

### INTRODUCTION

The homogenizing emulsifier makes use of the high shear emulsifier to distribute one or several phases to another continuous phase rapidly and even when the materials are under the vacuum condition.

The materials are processed in the narrow space between stator and rotor by strong energy of motion produced by the mechanical effect. By the operation of hydraulic shearing, centrifugal extruding, impacting, breaking and turbulence for over 100 thousand times per minute, the materials will be dispersed and emulsified instantly and evenly. After reciprocating circulation at high frequency, the fine finished products will be of high quality and without bubbles.

This model has a fixed pot and is equipped with a bottom homogenizer with internal and external circulation.

**KEYWORDS** [Fixed type](#) | [Homogenizer](#) | [Emulsifier](#) | [Vacuum](#) | [Capacity](#)



**ATTRIBUTES**

- Designed with a stable and compact structure, making it suitable for installation in limited space environments while ensuring reliable performance.
- Equipped with a high-speed homogenizing motor, the emulsifier delivers powerful shear forces to break down particles and achieve uniform dispersion of ingredients, resulting in fine emulsions with excellent stability and texture.
- Customers can choose from a range of configurations and options to suit their specific production requirements, including varying capacity options, control systems, and additional features such as heating and cooling capabilities.
- Built with high-quality components and precision engineering, the emulsifier offers reliable performance, durability, and longevity, providing customers with a cost-effective solution for their homogenization needs.

**TECHNICAL PARAMETERS**

Model		SME-B200	SME-B500	SME-B1000	SME-B2000
Capacity		200L	500L	1000L	2000L
Homogenizer motor	KW	6.5-8	6.5-8	9-11	11-14
	r/min	1440/2880	1440/2880	1440/2880	1440/2880
Stir motor	KW	2.2	4	5.5	5.5
	r/min	0-63	0-63	0-63	0-63
Dimension (mm)		3100x3000x2500	3850x3600x2750	4200x3850x3300	4500x4050x3800
Total power	Steam heating	15KW	22KW	28KW	34KW
	Electric heating	45KW	61KW	88KW	-
Limit vacuum		-0.09	-0.08	-0.08	-0.08

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

**CONNECT WITH US**

+86 577 6688 6278 | [info@capsulatech.com](mailto:info@capsulatech.com) | [www.captksolutions.com](http://www.captksolutions.com)